

REPEL 4220 SUPER PERFORMING PENETRATING SEALANT

1. Description

REPEL 4220 is a clear and transparent premium performance penetrating impregnating agent specially formulated to protect porous natural and dimensional stone such as rough, splif-faced, textured, acid-washed, honed, flame finished and sandblasted marble, granite, slate, sandstone, limestone, and quartzite, against stains, dust, dirt, water, acid rain, chemical attack, mildew, fungus, U.V. rays, salt, oil, tar and damage from efflorescence. Surface dirt should be removed using standard maintenance procedures. It allows moisture vapor transmission. REPEL 4220 also protects from freeze/thaw damage such as spalling, cracking and bubbling rendered by the harshest climates. It serves to densify the surface of any stone and yet offers no appearance change. REPEL 4220 is not a sealer and as such leaves no surface film to peel or yellow. This product also serves as an anti-graffiti agent. Surfaces treated with this product have a higher co-efficient of friction, therefore polished stone surfaces such as floors become less slippery.

2. Features and Advantages

- Provides Invisible Protections
- Treated surfaces develop hydrophobic properties
- Treated surfaces develop oleophobic properties

3. Recommended Surfaces

Can be applied on surfaces such as:

- Rough, split-faced, textured, acid-washed, honed, flame finished and sand blasted marble
- Granite
- Slate
- Sandstone
- Limestone
- Quartzite

4. Coverage

250 ft² (23 m²) to 450 ft² (41 m²) per 1.06 US Quart (1 L) depending on the surface treated.

5. Uses

1. For interior and exterior use.
2. For floors, walls, counter tops, roofs, ceilings and furniture manufacture from natural stone.
3. May also be used as a grout release agent.

®
DYNA

DYNA

NAFTA Region 5289 Highway #7 P.O. Box
56545, Woodbridge (ON) Canada L4L 8V3

CARICOM Region Lot 19, Naggo Head
Industrial Estate, Bridgeport Post Office,
St. Catherine, Jamaica

Phone: (905) 761-3309
Fax: (905) 761-2114

REPEL 4220 SUPER PERFORMING PENETRATING SEALANT

6. Limitations

1. Do not apply before 10 days following the completion of the work.
2. Certain types of slates and natural stone may darken slightly with the effect that the color will be enhanced, ensure that you always test first to determine if this is what you desire.
3. Do not apply below 0 °C (32 °F) or above 40 °C (104 °F).
4. Not to be used to provide oleophobic properties to surface to be treated. Use REPEL 4220 or SUPER IMPREGNATOR 4210 instead.
5. Not to be used to enhance the color of the surface to be treated. Use TerraSeal Matte 4300, TerraSeal Gloss 4320, TerraCotta 4330 or ANTIQUA 4350 instead.
6. Not to be used to guard against hydrostatic pressure.

7. Application

Wash the surface that is to be treated and let dry completely before application. Wash with DYNA brand of cleaners. Ensure that the surface is completely dry and there is no residual moisture present. Apply REPEL 4220 evenly over the surface using a clean dry cloth, brush, roller or spray on. Permit the product to absorb into the surface for at least one half hour. For polished surfaces wipe up the excess and buff up with a clean dry cloth after the product had a chance to absorb into the surface. Non-polished surfaces need not have the excess wiped up. Let dry and do not permit heavy foot traffic for at least 24 hours. For maximum protection a repeat application is recommended. If no grout release agent will be used for natural stone then this product must be applied at least once PRIOR to grouting.

8. Packaging

DYNA's REPEL 4220 is available in 1 L (1.06 US quarts), 3.78 L (1 US gallon), 18.9 L (5 US gallons)

9. Cautions

Contains petroleum distillates. If swallowed, give plenty of air and call physician immediately. This product is combustible. Keep away from open heat, sparks, and open flames. Ensure that the work area is properly ventilated until the product fully cures. Turn off all pilot lights or sources of ignition that may ignite this product. Avoid contact with skin and eyes. If product contacts skin flush with plenty of water. If product comes in contact with eyes flush with plenty of water and consult a physician immediately. **Keep out of reach of children**

10. Limited Warranty

This premium quality product was designed to satisfy the user. If you are not satisfied after Surface Testing on a small area, please contact our technical service department immediately. **NO WARRANTIES** expressed or implied are offered by DYNA. The Manufacturer's liability is limited to the replacement of products proven defective. The user assumes all risks and liabilities associated with the use of this product.

[®]
DYNA

DYNA

NAFTA Region 5289 Highway #7 P.O. Box
56545, Woodbridge (ON) Canada L4L 8V3

CARICOM Region Lot 19, Naggo Head
Industrial Estate, Bridgeport Post Office,
St. Catherine, Jamaica

Phone: (905) 761-3309
Fax: (905) 761-2114

REPEL 4220 SUPER PERFORMING PENETRATING SEALANT

11. Notice

DYNA shall not be liable for incidental and consequential damages indirectly or directly sustained, nor for any loss or injury by the application of this product or for any other intended use. Before using, the user shall determine the suitability of the product for its intended use and the user will assume all risks and liabilities that may arise in connection therewith. DYNA's liability is expressly limited to the replacement of products proven defective.

12. Technical Support

If you have any questions or if you need any additional information on DYNA's products, please consult our website www.dyna.ca or reach us by e-mail at : mail@dyna.ca

NAFTA Region

DYNA Metro Inc.
5289 Hwy 7, Suite # 7,
P.O. Box 56545
Woodbridge, Ontario,
Canada L4L 8V3

CARICOM Region

DYNA Metro Inc.
Lot 19, Naggo Head
Industrial Estate,
Portmore,
St. Catherine, Jamaica

DYNA[®]

DYNA

NAFTA Region 5289 Highway #7 P.O. Box
56545, Woodbridge (ON) Canada L4L 8V3

CARICOM Region Lot 19, Naggo Head
Industrial Estate, Bridgeport Post Office,
St. Catherine, Jamaica

Phone: (905) 761-3309
Fax: (905) 761-2114