

GROUT GUARD 4100 GROUT SEALER AND PROTECTOR

1. Description

GROUT GUARD 4100 is a premium performing Silane/Siloxane water-borne grout sealer and protector. It will protect from many items, which may stain your grout joints and also from acid rain, dirt, mildew, fungus, salt, efflorescence, It provides 100 % moisture vapour transmission, which is important for exterior tile work. It will increase freeze / thaw resistance and protect from spalling, cracking and bubbling of your grout joints rendered by the harshest climates. It will not yellow and offers no surface appearance change to your grout joints. It will extend the life of your grout joints by many years.

2. Uses

For interior and exterior use. Can be used for floor, wall, counter top, and ceiling grout joints.

3. Available Packaging

500 ml Spray Bottle

4. Coverage

200 ft² to 600 ft² per litre, depending on the absorbency, quality and the type of grout joints.

5. Limitations

1. Not to be used to guard against hydrostatic pressure.
2. Do not apply before 10 days following the completion of the work.
3. Do not apply below 5°C (40°F) or above 40°C (104°F).
4. Not to be used for chemical grouting. Only effective on cementitious type of grouting.

6. Main Application

1. Ensure that the grout joints are clean and thoroughly dry prior to application. Use DYNA brand of cleaners to clean the grout joints.
2. Apply GROUT GUARD 4100 evenly over the grout surface by spraying.
3. Wipe off excess material that sprayed on your tilework.
4. Allow the sealer to sit and absorb on the surface of the grout joints for 5 to 10 minutes.
5. Wipe up excess from the surface of the grout joints.
6. A repeat application is recommended.
7. Allow to cure for 24 to 48 hours.

7. Cleaning

Clean hands and tools with clean water.

[®]
DYNA

DYNA

NAFTA Region 5289 Highway #7 P.O. Box
56545, Woodbridge (ON) Canada L4L 8V3

CARICOM Region Lot 19, Naggo Head
Industrial Estate, Bridgeport Post Office,
St. Catherine, Jamaica

Phone: (905) 761-3309
Fax: (905) 761-2114

GROUT GUARD 4100 GROUT SEALER AND PROTECTOR

TECHNICAL
DATA
SHEET

Updated: Mar 2nd 2017

8. Caution

If swallowed call a physician immediately. If splashed in eyes or skin rinse with plenty of water.

Keep out of reach of children

9. Limited Warranty

This premium quality product was designed to satisfy the user. If you are not satisfied after Surface Testing on a small area, please contact our technical service department immediately. **NO WARRANTIES** expressed or implied are offered by DYNA. The Manufacturer's liability is limited to the replacement of products proven defective. The user assumes all risks and liabilities associated with the use of this product.

10. Notice

DYNA shall not be liable for incidental and consequential damages indirectly or directly sustained, nor for any loss or injury by the application of this product or for any other intended use. Before using, the user shall determine the suitability of the product for its intended use and the user will assume all risks and liabilities that may arise in connection therewith. DYNA's liability is expressly limited to the replacement of products proven defective.

11. Technical Support

If you have any questions or if you need any additional information on DYNA's products, please consult our website www.dyna.ca or reach us by e-mail at : mail@dyna.ca

NAFTA Region

DYNA Metro Inc.
5289 Hwy 7, Suite # 7,
P.O. Box 56545
Woodbridge, Ontario,
Canada L4L 8V3

CARICOM Region

DYNA Metro Inc.
Lot 19, Naggo Head
Industrial Estate,
Portmore,
St. Catherine, Jamaica

®
DYNA

DYNA

NAFTA Region 5289 Highway #7 P.O. Box
56545, Woodbridge (ON) Canada L4L 8V3

CARICOM Region Lot 19, Naggo Head
Industrial Estate, Bridgeport Post Office,
St. Catherine, Jamaica

Phone: (905) 761-3309
Fax: (905) 761-2114

? Questions: WWW.DYNA.CA
mail@dyna.ca

866-861-6424